

THEORICAL REEL CAPACITY (ft) ACCORDING TO PRODUCT DIAMETER (in)

.520				505	1,010	2,160	3,239	3,194	4,294	4,648
.530					968	2,069	3,103	3,059	4,113	4,463
.540					928	1,983	2,975	2,933	3,944	4,289
.550					890	1,903	2,855	2,815	3,784	4,125
.560					855	1,828	2,742	2,703	3,634	3,970
.570					822	1,757	2,635	2,598	3,493	3,824
.580					791	1,690	2,535	2,499	3,360	3,686
.590					761	1,627	2,440	2,406	3,235	3,555
.600					733	1,567	2,351	2,318	3,116	3,431
.610					707	1,511	2,266	2,234	3,004	3,314
.620					682	1,457	2,186	2,155	2,897	3,202
.630					658	1,407	2,110	2,080	2,797	3,096
.640					636	1,358	2,038	2,009	2,701	2,995
.650					614	1,313	1,969	1,941	2,610	2,899
.660					594	1,269	1,904	1,877	2,524	2,807
.670					575	1,228	1,842	1,816	2,442	2,720
.680					556	1,189	1,783	1,758	2,364	2,637
.690					539	1,151	1,727	1,703	2,289	2,557
.700					522	1,116	1,674	1,650	2,218	2,482
.710					506	1,082	1,622	1,599	2,151	2,409
.720						1,049	1,574	1,551	2,086	2,339
.730						1,018	1,527	1,505	2,024	2,273
.740						988	1,482	1,461	1,965	2,209
.750						960	1,440	1,419	1,908	2,148
.760						933	1,399	1,379	1,854	2,090
.780						907	1,360	1,341	1,802	2,007
.800						882	1,322	1,304	1,753	1,930
.820						858	1,286	1,268	1,705	1,857
.840						835	1,252	1,234	1,659	1,788
.860						812	1,219	1,201	1,615	1,724
.880						791	1,187	1,170	1,573	1,662
.900						751	1,127	1,111	1,493	1,584
.920						714	1,071	1,056	1,420	1,510
.940						680	1,019	1,005	1,351	1,442
.960						648	971	958	1,288	1,379
.980						618	927	914	1,229	1,319
1						590	885	873	1,173	1,263
1.05						564	846	834	1,122	1,176
1.1						540	810	798	1,074	1,099



omerin

OMERIN USA, Inc. QS Technologies division
95 Research Parkway, Meriden,
Connecticut 06450
Phone: 203-237-2297
qstech@omerin.com

www.omerin.com

® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.